Chromate Free Magnesium Gearbox Protection System

Brad Wiley

ASETSDefense November 2014

© 2014 Rolls-Royce Corporation

The information in this document is the property of Rolls-Royce Corporation and may not be copied or communicated to a third party, or used for any purpose other than that for which it is supplied without the express written consent of Rolls-Royce Corporation.

This information is given in good faith based upon the latest information available to Rolls-Royce Corporation, no warranty or representation is given concerning such information, which must not be taken as establishing any contractual or other commitment binding upon Rolls-Royce Corporation or any of its subsidiary or associated companies.



maintaining the data needed, and including suggestions for reducing	llection of information is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar OMB control number.	ion of information. Send comments arters Services, Directorate for Info	s regarding this burden estimate or primation Operations and Reports	or any other aspect of the 1215 Jefferson Davis	nis collection of information, Highway, Suite 1204, Arlington	
1. REPORT DATE		A DEDODE TYPE	ADT TANDE	3. DATES COVERED		
NOV 2014		2. REPORT TYPE		00-00-2014 to 00-00-2014		
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
Chromate Free Magnesium Gearbox Protection System				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Rolls-Royce Corporation,62 Buckingham Gate,London, SW1E 6AT, England,				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited						
13. SUPPLEMENTARY NOTES ASETSDefense 2014: Sustainable Surface Engineering for Aerospace and Defense, 18-20 Nov 2014, Fort Myer, VA.						
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF ABSTRACT				18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON	
a. REPORT	b. ABSTRACT	c. THIS PAGE	Same as	24	RESPONSIBLE PERSON	
unclassified	unclassified	unclassified	Report (SAR)			

Report Documentation Page

Form Approved OMB No. 0704-0188


Outline

- Magnesium: Why mag?
- Application
- Challenging Feature
- Legacy System
- Candidates
- New System
- Functional Requirements, Tests and Results
- Examples of Tests
- Benefits and conclusions



Why magnesium?

- Lightest of the structural metals
 - ½ of steel
 - 1/3 of aluminum
- World production: ~400,000 ann
- No limit:
 - 8th most common element
 - 6th most abundant metal
 - Sea water contains ~0.15% mag
- Recycling requires only 5% OEM
- The BMW N52 (st6 dohc engine) crankcase shell since 2004. Ref 1
- Since 1936, VW has used cast mag



Tast Tacts: Magnesium Alloy Engine

- Magnesium alloy engine was produced in 300,000 BMW vehicles in 2006
- Magnesium alloy crankcase is 24 percent lighter than conventional aluminum engine
- Engine achieves increased power output and higher torque



The R6 Composite Magnesium-Aluminum alloy engine is the mainstay of BMW's vehicle fleet.

- Environmental benefits are reduced fuel consumption and CO₂ emissions
- » R6 is lightest 3.0 liter inline six-cylinder gasoline engine in the world
- Magnesium alloy engine block and bedplate with aluminum cylinder inserts
- BMW foundry recycles 40 percent of its magnesium (9,000 tons per year)
- N R6 composite magnesium-aluminum alloy crankcase received the International Magnesium Association's Award of Excellence





Why protect magnesium?











The AE2100D3 engine




PGB – Propeller Gear Box GMAD – Gearbox Mounted Accessory Drive







Split line illustration





Legacy coating system

Oil Wetted Surfaces

Dichromate


Split Lines / Machined Surfaces Silicone Resin over HAE






External Cast Surfaces

Top Coat over HAE







Legacy coating system

- HAE
 - Patented in 1952 (by Harry A. Evangelitis)
 - Corrosion resistance
 - Surface finish
- Complex masking scheme for application
- Regulatory pressures
 - Hexavalent Cr sustainability issue
 - High VOC content in solvents

A comprehensive replacement of the legacy coating was needed

- Improved thickness consistency
- Improved unit cost
- Lessened environmental impact
- Improved corrosion performance and aftermarket cost





Proposed coating system

- Anodize
 - Tagnite 8200 Type 1 (AMS 2466)
- Paint
 - Indestructible Paint Ltd
 Chromate free Low VOC 985 series
 - Sealer (green tinted)
 - Primer
 - Top Coat



Tagnite - What is it?







Rockhard - What is it?








Proposed coating system


Internal Oil Wetted Surfaces

Sealer over Tagnite



Split Line /Machined Surfaces

Top Coat, Primer & Sealer over Tagnite




External Cast Surfaces

Top Coat, Primer & Sealer over Tagnite

Mount Material


Rockhard Topcoat layers

Rockhard Primer Rockhard Sealer Tagnite





Side by side look at coating schemes








Functional Criteria, Tests and Results

- Coating Adhesion- PASS
 - ASTM D3359 Method B
- Corrosion Resistance- PASS
 - Neutral Salt Spray: ASTM B117, ASTM D714, ASTM D1654
 - Cyclic Salt Spray:
- Thermal Stability (430°F, 1000 hrs)- PASS
 - ASTM D714
- Fluid Resistance (fuel, oil, hydraulic)- PASS
 - ISO 2812-1
- Damage Resistance (impact, bend, corner radii)- PASS
 - ASTM D2794, ASTM D522, Rolls-Royce Corp Test Method
- Releasability (Ease of Disassembly)- PASS w/ use of Frekote 700-NC
 - Rolls-Royce Corp Test Method (per IR 37340)
- Repairability (after damage and touch-up repair)- PASS w/ Brush Tagnite
 - Adhesion: ASTM D3359 Method B
 - Neutral Salt Spray: ASTM B117, ASTM D714, ASTM D1654
 - Metallographic
- Fatigue Testing (bar)- PASS
- Torque Testing (scrap part)- PASS
- Engine Test (assembly/leak check)- PASS




Magnesium panels for environmental testing





Corrosion testing – anodize coatings

Panel Type A



HAE after 24 hrs.



HAE after 96 hrs.



Tagnite (panel 1) after 24 hrs.



Tagnite (nanel 1) after 96 hr



Tagnite (panel 2) after 24 hrs.




Tagnite (panel 1) after 96 hrs Tagnite (panel 2) after 96 hrs.

criteria: Coating shall receive a rating of 9 after exposure to 24 hours in neutral salt spray AND the new coating system shall meet or exceed the performance of the old coating configuration.

Result: Pass



Corrosion testing – external surfaces



Panel Type D



Panel Type D



New Coating

Criteria: Coating shall receive a rating of 7 after exposure to 250 hours in neutral salt spray AND the new coating system shall meet or exceed the performance of the old coating



Legacy



Legacy

Legacy



New Coating


Result: Pass

configuration.




Fluid Resistance

Rockhard Sealer- Panel Type B





Before



After Rockhard Top Coat- Panel Type D





Criteria: All panels shall show no visual signs of blistering or lifting after exposure to fuel (Jet A) and hydraulic fluid (Royco 782).

Results: Pass


Fuel: 70°C, 163 hrs

Hydraulic Fluid: 70°C, 189 hrs




Impact damage resistance

Panel Type B



Rockhard


Panel Type D



Panel Type C








Legacy

Criteria: There shall be no cracking or detachment at an indentation depth of 3.8 mm (.15 inch) using a 1000±1 g punch AND the new coating system shall meet or exceed the performance of the old coating configuration.

Result: Pass



Fatigue performance



Criteria:


No increase in fatigue debit over legacy or baseline coating.

Result: Pass



Repair and Overhaul

 Plastic Media Blast removal process successful in removing the paint without removing the anodize



Cross section of a painted panel partially stripped via plastic media blasting



Higher magnification view of the remaining conversion coating

Criteria: The coating shall be strippable and be capable of supporting subsequent re-paint

Results: PASSES



Engine Test

- Purpose
 - Assembly/fit check
 - Leak check
- Testing details
 - Prop Stand test
 - Post-engine test inspection
- Results
 - After 3 tear downs and 150 hours
 - New coating configuration PASSES



Conclusion:

It's in production!

- Performance improvement
- Environmental liability eliminated
- **Unit Cost neutral**
- Improvement in Aftermarket costs









Ref 7: http://www.corrosionist.com/galvanic_corrosion_chart.htm Ref 2: www.intlmag.org/showcase/mg001.pdf Ref 8 http://airandspace.si.edu/webimages/highres/5013h.jpg

Ref 3: http://vwparts.aircooled.net/OEM-VW-Magnesium-Engine-Case-

Ref 9: Corrosion and Materials, Vol 30 No 6, 2 December 2005 ISSN 1326-193

043-101-0250E-p/oem-vw-engine-case.htm

Ref 10 http://www.arl.army.mil/www/default.cfm?page=375

Ref 4: http://www.fwtec.com/FW/nanosolution.html# Ref 5: Rolls-Royce Front Frame example

Ref 6: http://www.volksworld.com/blog/staff-blogs/jons-blog/strippingdown-a-donor-beetle-engine/



Questions?

Ref 1: http://www.magnesium-elektron.com/about-magnesium.asp?ID=1

Ref 2: www.intlmag.org/showcase/mg001.pdf

Ref 3: http://wwparts.aircooled.net/OEM-VW-Magnesium-Engine-Case-043-101-025OE-p/oem-vw-engine-case.htm

Ref 4: http://www.fwtec.com/FW/nanosolution.html#

Ref 5: Rolls-Royce Front Frame example

Ref 6: http://www.volksworld.com/blog/staff-blogs/jons-blog/stripping-down-a-donor-beetle-engine/

Ref 7: http://www.corrosionist.com/galvanic_corrosion_chart.htm Ref 8 http://airandspace.si.edu/webimages/highres/5013h.jpg Ref 9: Corrosion and Materials, Vol 30 No 6, 2

December 2005 ISSN 1326-193
Ref 10 http://www.arl.army.mil/www/default.cfm?page=375

